



PRO | EDGE™

 Thin Clients

5-Year Warranty Best Warranty in the Industry

For 30 years, I-O Corporation has been known in the IT community for providing customers with highly reliable products. With that legacy, I-O's ProEdge thin clients offer the peace of mind of a 5-year warranty. Not only is ProEdge reliable, it is *Small, Simple and Secure*.



Small Footprint and Total Cost of Ownership

With dimensions that are about the size of a three CD set, **ProEdge** occupies a small space on a desktop or attaches to the back of a standard LCD monitor. Despite its small size, **ProEdge** offers the flexibility of XPe, CE, and Linux operating systems and the convenience of wireless connectivity.

In addition to having a small price tag, **ProEdge** thin clients save time and money. System administrators save time by configuring, managing, and updating **ProEdge** from a central location. **ProEdge** saves money by using significantly less electricity and producing less heat than PC's.

Simple to Manage and Deploy

To make things really simple, **ProEdge** offers Symantec's™ Altiris® Deployment Solution™. As a leading client management tool, Altiris provides console and web-based control, reporting, alerting, policy driven software delivery, patch management, and other Altiris lifecycle management solutions.

Secure ProEdge Thin Clients

An IT manager has the option to remotely disable access to any USB mass storage device attached to a **ProEdge** thin client. This security advantage prevents employees from introducing unauthorized or dangerous files to the network and protects sensitive information from being copied.

With three decades of experience in display technology, I-O Corporation continues its commitment to excellence by offering powerful thin clients that are *small, simple, and secure*.



Altiris Solutions
VERIFIED





PRO | EDGE™

Thin Clients
Specifications & Features

Base Models

HARDWARE	ProEdge L5	ProEdge L8	ProEdge L15	ProEdge C5	ProEdge C8	ProEdge C15	ProEdge X8	ProEdge X15
Operating System	LINUX	LINUX	LINUX	CE 5.0	CE 5.0	CE 5.0	XPE	XPE
Processor	AMD Geode™ GX533	AMD Geode™ LX800	VIA C7 1.5 GHz	AMD Geode™ GX533	AMD Geode™ LX800	VIA C7 1.5 GHz	AMD Geode™ LX800	VIA C7 1.5 GHz
Ram	128 MB	128 MB	512 MB	128 MB	128 MB	256 MB	256 MB	512 MB
Ram Upgrade (Up to)	NA	1 GB	1 GB	NA	1 GB	1 GB	1 GB	1 GB
Flash	128 MB	128 MB	1 GB	64 MB	64 MB	64 MB	512 MB	1 GB
Flash Upgrade (Up to)	8 GB	8 GB	8 GB	8 GB	8 GB	8 GB	8 GB	8 GB
Video Port	DB 15	DB 15	DVI	DB 15	DB 15	VGA	DB 15	DVI
Display Resolution (Up to)	1600x1200	1920x1440	1920x1200	1600x1200	1920x1440	1920x1200	1920x1440	1920x1200
USB Ports	2 rear*, 2 front*	2 rear, 2 front	2 rear, 2 front	2 rear*, 2 front*	2 rear, 2 front	2 rear, 2 front	2 rear, 2 front	2 rear, 2 front
Ethernet	10/100	10/100	10/100	10/100	10/100	10/100	10/100	10/100
Microphone Port	✓	✓	✓	✓	✓	✓	✓	✓
Speaker Port	✓	✓	✓	✓	✓	✓	✓	✓
Mouse	✓	✓	✓	✓	✓	✓	✓	✓
104 Key Keyboard	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
122 Key Keyboard	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Wireless 802.11 b/g	NA	NA	NA	NA	Optional	Optional	NA	NA
Wireless 802.11 a/b/g	NA	Optional	Optional	NA	NA	NA	Optional	Optional
LCD Mounting Bracket	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
USB to Serial Adapter	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
USB to Parallel Adapter	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
USB Dual Monitor Adapter	NA	NA	NA	NA	NA	NA	Optional	Optional

*USB Type 1.1

SOFTWARE

RDP/ICA	✓	✓	✓	✓	✓	✓	✓	✓
I-O Configuration Utility	✓	✓	✓	✓	✓	✓	✓	✓
Altiris Client†	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Browser and E-mail	Optional	Optional	Optional	Optional	Optional	Optional	✓	✓
Viewers	NA	NA	NA	Optional	Optional	Optional	Downloadable	Downloadable
Terminal Emulation Suite	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional

†Requires Altiris Deployment Solution v 6.8 (build 282) or newer.

ENVIRONMENT

Output Power	12 VDC, 1.2 A	12 VDC, 1.2 A	12 VDC, 3.5 A	12 VDC, 1.2 A	12 VDC, 1.2 A	12 VDC, 3.5 A	12 VDC, 1.2 A	12 VDC, 3.5 A
Dimensions	1.5x6x5.3 in	1.5x6x5.3 in	1.7x5.5x5.1 in	1.5x6x5.3 in	1.5x6x5.3 in	1.7x5.5x5.1 in	1.5x6x5.3 in	1.7x5.5x5.1 in
Weight	.8 lbs	.8 lbs	1.2 lbs	.8 lbs	.8 lbs	1.2 lbs	.8 lbs	1.2 lbs
All Models	Input Power: 90-240 VAC, 50/60 Hz; Operating Temperature: 10°-30° C, 50°-90° F; Humidity: 0-90% non-condensing; Regulatory: FCC Class A, CE, RoHS							

Features & Benefits

- **5-Year Warranty:** Offers longevity, investment protection and peace of mind.
- **USB Management:** An IT manager can remotely disable access to all USB mass storage devices, preventing unauthorized files from being introduced to the network. In addition, confidential files cannot be copied.
- **Managed by Symantec's Altiris:** Provides a comprehensive central client management tool that offers control, reporting, alerting, policy driven software delivery, patch management, and more.
- **Total Cost of Ownership:** Economical to manage and support. Low power consumption and heat output.
- **Small Footprint:** Occupies a small amount of valuable desktop space. Mountable on the back of a VESA standard LCD monitor.
- **Flexibility:** Offers a choice of operating systems (Linux, CE and XPe), processor speeds, memory sizes and more.
- **Wireless Option:** ProEdge offers the flexibility of wireless 802.11 connectivity.